



US006025654A

United States Patent [19][11] **Patent Number:** **6,025,654****Roppel et al.**[45] **Date of Patent:** **Feb. 15, 2000**

[54] **METHOD FOR CONTROLLING THE TRANSMISSION OF DATA BETWEEN COMPONENTS AND COMPONENT FOR IMPLEMENTING THE METHOD**

[56] **References Cited****U.S. PATENT DOCUMENTS**

[75] Inventors: **Rüdiger Roppel**, Hildesheim; **Detlef Rode**, Hemmingen, both of Germany

5,848,367 12/1998 Lotocky et al. 701/36

[73] Assignee: **Robert Bosch GmbH**, Stuttgart, Germany

Primary Examiner—Richard T. Elms*Attorney, Agent, or Firm*—Fulbright & Jaworski, LLP[21] Appl. No.: **08/852,232**[57] **ABSTRACT**[22] Filed: **May 6, 1997**[30] **Foreign Application Priority Data**

Jun. 24, 1996 [DE] Germany 196 25 103

[51] Int. Cl.⁷ **B60L 1/00**[52] U.S. Cl. **307/10.1; 340/825; 701/1**

[58] Field of Search 307/9.1–10.8;
701/1, 29, 32–36, 45, 49; 359/123, 142,
146, 173; 340/825, 825.02, 825.03, 825.06,
438

A method for controlling the transmission of information between components, preferably in a motor vehicle, these components being either data sources or data sinks, wherein a double cascade separates the data transmission of the service components and from that of the music components. The data of the two data cascades can be mixed by means provided in the audio/video sink.

15 Claims, 4 Drawing Sheets